

# SGS

4.5Ø x 14.5 mm

Fast-Acting Fuse



## Agency Approvals

Agency	Ampere Rating
UL Listed	10mA - 3.5A
CSA Certified	10mA - 3.5A
PSE	1A - 3.5A

## Interrupting Rating

100mA - 3.5A:	10,000 amperes at 125V AC
100mA - 1A:	35 amperes at 250V AC
1.1A - 3.5A:	100 amperes at 250V AC

## Product Characteristics

Operating Temperature	-55 °C to 125 °C
Material	Body: Glass / Caps: Nickel Plated Brass


## Electrical Characteristics

Ampere Rating	Opening Time		
	1 In	1.35 In	2 In
	MIN	MAX	MAX
100mA - 10A	4 hr	1 hr	5 sec

## Packaging

Packaging Option	Quantity
Bulk	2,000 pcs / box

## Mechanical Dimensions (mm)



# SGP-A

4.5Ø x 14.5 mm

Fast-Acting Fuse



## Agency Approvals

Agency	Ampere Rating
UL Listed	10mA - 3.5A
CSA Certified	10mA - 3.5A
PSE	1A - 3.5A

## Interrupting Rating

100mA - 3.5A:	10,000 amperes at 125V AC
100mA - 1A:	35 amperes at 250V AC
1.1A - 3.5A:	100 amperes at 250V AC

## Product Characteristics

Operating Temperature	-55 °C to 125 °C
Material	Body: Glass / Caps: Nickel Plated Brass
Leads Wire	Ø0.63 mm 7A and less. Ø1.0 mm for rating above 8A.

## Electrical Characteristics

Ampere Rating	Opening Time		
	1 In	1.35 In	2 In
	MIN	MAX	MAX
100mA - 10A	4 hr	1 hr	5 sec

## Packaging

Packaging Option	Quantity
Bulk	500 pcs / box
On Axial Tape & Reel	1,000 pcs / box

## Mechanical Dimensions (mm)

