

# SPECIFICATIONS

<b>Customer</b>	
<b>Product Name</b>	<b>Wire Wound SMD Power Inductor</b>
<b>Sunlord Part Number</b>	<b>SWPA5040S Series</b>
<b>Customer Part Number</b>	

New Released,  Revised]                      SPEC No. .: SWPA0801230000

【This SPEC is total 17 pages.】  
 【ROHS Compliant Parts】

Approved By	Checked By	Issued By

## Shenzhen Sunlord Electronics Co., Ltd.

Address: Sunlord Industrial Park, Dafuyuan Industrial Zone, Baoan, Shenzhen, China    518110  
 Tel: 0086-755-29832333                      Fax: 0086-755-82269029                      E-Mail: sunlord@sunlordinc.com

**【For Customer approval Only】**    Date: \_\_\_\_\_

Qualification Status:     Full     Restricted     Rejected

Approved By	Verified By	Re-checked By	Checked By

Comments:  
 \_\_\_\_\_

**【Version change history】**

Rev.	Effective Date	Changed Contents	Change Reasons	Approved By
01	/	New released	/	Guo Ouyang

#### Caution

All products listed in this specification are developed, designed and intended for use in general electronics equipment. The products are not designed or warranted to meet the requirements of the applications listed below, whose performance and/or quality require especially high reliability, or whose failure, malfunction or trouble might directly cause damage to society, person, or property. Please understand that we are not responsible for any damage or liability caused by use of the products in any of the applications below. Please contact us for more details if you intend to use our products in the following applications.

1. Aircraft equipment
2. Aerospace equipment
3. Undersea equipment
4. nuclear control equipment
5. military equipment
6. Power plant equipment
7. Medical equipment
8. Transportation equipment (automobiles, trains, ships,etc.)
9. Traffic signal equipment
10. Disaster prevention / crime prevention equipment
11. Applications of similar complexity or with reliability requirements comparable to the applications listed in the above

**1. Scope**

This specification applies to the SWPA5040S Series of wire wound SMD power inductor.

**2. Product Description and Identification (Part Number)**

1) Description:

SWPA5040S series of Wire wound SMD power inductor.

2) Product Identification (Part Number)

SWPA 5040 S □□□ □ I □□□  
 ① ② ③ ④ ⑤ ⑥ ⑦

①	Type	
SWPA	Wire wound SMD power inductor	

②	External Dimensions(L×W×H) [mm]	
5040	5.0X5.0X 4.0	

③	Feature type	
S	Standard Type	

④	Nominal Inductance	
Example	Example	
1R0	1.0uH	
100	10uH	
101	100uH	

⑤	Inductance Tolerance	
N	±30%	
M	±20%	

⑦	Special Process code	
□□□	Special Process code	
* Standard product is blank		

⑥	Packing	
T	Tape Carrier Package	

**3 Electrical Characteristics**

Please refer to **Appendix A** (Page 13).

- Operating and storage temperature range (individual chip without packing): -40°C ~+125°C (Including Self-heating) .
- Storage temperature range (packaging conditions): -10°C~+40°C and RH 70% (Max.).

**4 Shape and Dimensions**

- Dimensions and recommended PCB pattern for reflow soldering, please see **Fig.4-1** and **Table 4-1**.
- Structure <sub>B</sub> See **Fig.4-3** and **Table 4-2**.




Fig.4-1

[Table 4-1] (Unit: mm)

Series	A	B	C	D	E	a.	b.	c
SWPA5040S	5.0±0.2	5.0±0.2	4.0 Max.	4.0±0.2	1.25±0.2	2.30 Typ.	1.40 Typ.	4.20 Typ.




Fig.4-2

Δf: Clearance between terminal and the surface of plate must be 0.2mm max when coil is placed on a flat plate.




Fig.4-3

[Table 4-2]

No.	Components	Material
①	Ferrite Core	Ni-Zn Ferrite
②	Wire	Polyurethane system enameled copper wire
③	Magnetic Glue	Epoxy resin and magnetic powder
④	Electrodes	Sn Alloy

5 Test and Measurement Procedures

5.1 Test Conditions

5.1.1 Unless otherwise specified, the standard atmospheric conditions for measurement/test as:

- a. Ambient Temperature: 20±15°C
- b. Relative Humidity: 65±20%
- c. Air Pressure: 86kPa to 106kPa

5.1.2 If any doubt on the results, measurements/tests should be made within the following limits:

- a. Ambient Temperature: 20±2°C
- b. Relative Humidity: 65±5%
- c. Air Pressure: 86kPa to 106kPa

5.2 Visual Examination

Inspection Equipment: 10X microscope.

5.3 Electrical Test

5.3.1 Inductance (L)

- a. Refer to **Appendix A**. Test equipment: WK3260B LCR meter or equivalent.
- b. Test Frequency and Voltage: refers to **Appendix A**.

5.3.2 Direct Current Resistance (DCR)

- a. Refer to **Appendix A**.
- b. Test equipment: HIOKI 3540 or equivalent.

5.3.3 Saturation Current (Isat)

- a. Refer to **Appendix A**
- b. Test equipment: WK3260B LCR meter or equivalent.

5.3.4 Temperature rise current (I<sub>rms</sub>)

- a. Refer to **Appendix A**.
- b. Test equipment (see Fig. 5.3.4-1, Fig. 5.3.4-2): Electric Power, Electric current meter, Thermometer.
- c. Measurement method
  1. Set test current to be 0 mA.
  2. Measure initial temperature of choke surface.
  3. Gradually increase current and measure choke temperature for corresponding current.
  4. Definition of Temperature rise current: DC current that causes the temperature rise (ΔT) from ambient temperature




Fig. 5.3.4-1




Fig. 5.3.4-2

5.3.5 Self-resonant frequency (SRF)

- a. Refer to **Appendix A**.
- b. Test equipment: Agilent E4991A+16197 or equivalent

6 Product Marking

Please refer to Fig. 6-1.

The content of marking please refers to **Appendix A**.








Fig. 6-1.

7 Reliability Test

Items	Requirements	Test Methods and Remarks
7.1 Terminal Strength	No removal or split of the termination or other defects shall occur.  <p style="text-align: center;"><b>Fig.7.1-1</b></p>	<ol style="list-style-type: none"> <li>① Solder the inductor to the testing jig (glass epoxy board shown in <b>Fig.7.1-1</b>) using eutectic solder. Then apply a force in the direction of the arrow.</li> <li>② 10N force.</li> <li>③ Keep time: 5s</li> </ol>
7.2 Resistance to Flexure	No visible mechanical damage.  <p style="text-align: center;"><b>Fig.7.2-1</b></p>	<ol style="list-style-type: none"> <li>① Solder the chip to the test jig (glass epoxy board) using eutectic solder. Then apply a force in the direction shown as <b>Fig.7.2-1</b>.</li> <li>② Flexure: 2mm</li> <li>③ Pressurizing Speed: 0.5mm/sec</li> <li>④ Keep time: 30±1s</li> <li>⑤ Test board size: 100X40X1.0</li> <li>⑥ Land dimension: Please see <b>Fig. 4-1</b></li> </ol>
7.3 Vibration	<ol style="list-style-type: none"> <li>① No visible mechanical damage.</li> <li>② Inductance change: Within ±10%</li> </ol>	<ol style="list-style-type: none"> <li>① Solder the chip to the testing jig (glass epoxy board shown as the following figure) using eutectic solder.</li> <li>② The chip shall be subjected to a simple harmonic motion having total amplitude of 1.5mm, the frequency being varied uniformly between the approximate limits of 10 and 55 Hz.</li> <li>③ The frequency range from 10 to 55 Hz and return to 10 Hz shall be traversed in approximately 1 minute. This motion shall be applied for a period of 2 hours in each 3 mutually perpendicular directions (total of 6 hours).</li> </ol>
7.4 Temperature coefficient	Inductance change: Within ±20%	<ol style="list-style-type: none"> <li>① Temperature: -40°C~+125°C</li> <li>② With a reference value of +20°C, change rate shall be calculated</li> </ol>
7.5 Solderability	90% or more of electrode area shall be coated by new solder.	<ol style="list-style-type: none"> <li>① The test samples shall be dipped in flux, and then immersed in molten solder.</li> <li>② Solder temperature: 245±5°C</li> <li>③ Duration: 5±1 sec.</li> <li>④ Solder: Sn/3.0Ag/0.5Cu</li> <li>⑤ Flux: 25% resin and 75% ethanol in weight</li> <li>⑥ Immersion depth: all sides of mounting terminal shall be immersed</li> </ol>
7.6 Resistance to Soldering Heat	<ol style="list-style-type: none"> <li>① No visible mechanical damage.</li> <li>② Inductance change: Within ±10%</li> </ol>	<ol style="list-style-type: none"> <li>① Re-flowing Profile: Please refer to <b>Fig. 7.6-1</b>.</li> <li>② Test board thickness: 1.0mm</li> <li>③ Test board material: glass epoxy resin</li> <li>④ The chip shall be stabilized at normal condition for 1~2 hours before measuring</li> </ol>  <p style="text-align: right;"><b>Fig. 7.6-1</b></p>


<p>7.7 Thermal Shock</p>	<p>① No visible mechanical damage. ② Inductance change: Within <math>\pm 10\%</math></p>  <p style="text-align: center;"><b>Fig.7.7-1</b></p>	<p>① Temperature and time: <math>-40\pm 3^{\circ}\text{C}</math> for <math>30\pm 3</math> min <math>\rightarrow 125^{\circ}\text{C}</math> for <math>30\pm 3</math> min, please refer to <b>Fig. 7.7-1</b>. ② Transforming interval: Max. 20 sec ③ Tested cycle: 100 cycles ④ The chip shall be stabilized at normal condition for 1~2 hours before measuring</p>
<p>7.8 Resistance to Low Temperature</p>	<p>① No visible mechanical damage ② Inductance change: Within <math>\pm 10\%</math></p>	<p>① Temperature: <math>-40\pm 3^{\circ}\text{C}</math> ② Duration: <math>1000^{\pm 24}</math> hours ③ The chip shall be stabilized at normal condition for 1~2 hours before measuring</p>
<p>7.9 Resistance to High Temperature</p>	<p>① No mechanical damage. ② Inductance change: Within <math>\pm 10\%</math></p>	<p>① Temperature: <math>125\pm 2^{\circ}\text{C}</math> ② Duration: <math>1000^{\pm 24}</math> hours ③ The chip shall be stabilized at normal condition for 1~2 hours before measuring.</p>
<p>7.10 Damp Heat</p>	<p>① No mechanical damage. ② Inductance change: Within <math>\pm 10\%</math></p>	<p>① Temperature: <math>60\pm 2^{\circ}\text{C}</math> ② Humidity: 90% to 95%RH ③ Duration: <math>1000^{\pm 24}</math> hours ④ The chip shall be stabilized at normal condition for 1~2 hours before measuring</p>
<p>7.11 Loading Under Damp Heat</p>	<p>① No mechanical damage. ② Inductance change: Within <math>\pm 10\%</math></p>	<p>① Temperature: <math>60\pm 2^{\circ}\text{C}</math> ② Humidity: 90% to 95% RH ③ Applied current: Rated current ④ Duration: <math>1000^{\pm 24}</math> hours ⑤ The chip shall be stabilized at normal condition for 1~2 hours before measuring</p>
<p>7.12 Loading at High Temperature</p>	<p>① No mechanical damage. ② Inductance change: Within <math>\pm 10\%</math></p>	<p>① Temperature: <math>85\pm 2^{\circ}\text{C}</math> ② Applied current: Rated current ③ Duration: <math>1000^{\pm 24}</math> hours ④ The chip shall be stabilized at normal condition for 1~2 hours before measuring</p>

**8 Packaging, Storage and Transportation**

**8.1 Tape and Reel Packaging Dimensions**

8.1.1 Taping Dimensions (Unit: mm)

Please refer to **Fig. 8.1.1** and **Table 8.1.1**.



**Fig. 8.1.1**

**[Table 8.1.1]**

Series	$A_0$	$B_0$	$W$	$E$	$F$	$P_0$	$P_1$	$P_2$	$D_0$	$T$	$K_0$
SWPA5040S	$5.3\pm 0.1$	$5.3\pm 0.1$	$12.0\pm 0.3$	$1.75\pm 0.1$	$5.5\pm 0.1$	$4.0\pm 0.1$	$8.0\pm 0.1$	$2.0\pm 0.1$	$1.5+0.1/-0.0$	$0.4\pm 0.03$	$4.2\pm 0.1$

8.1.2 Direction of rolling

Please refer to Fig. 8.1.2




Fig.8.1.2

8.1.3 Reel Dimensions (Unit: mm)

Please refer to Fig. 8.1.3.




Fig.8.1.3

8.1.4 Top tape strength

Peel-off strength: 10~130gf.

Peel-off angle: 165°~180°, refers to Fig.8.1.4.

Peel-off speed: 300mm/min.




Fig. 8.1.4

8.1.5 The number of components

A tape & reel package contains 1500 inductors.

8.1.6 The allowable number of empty chip cavities

Maximum two (2) chip cavities missing product may exist in a reel but they may not be consecutive two cavities.

8.2 Packing Documents and Marking

8.2.1 Packing Documents

Packing documents include the following:

- 1) Packaging list
- 2) Certificate of compliance (COC)

8.2.2 Packing QTY.

- 1) Inner Box: 1 reels in each box.
- 2) Outer Box: 2 or 4 inner boxes in each outer case.
- 3) 2 or 4 reels in each outer case.

8.2.3 Marking

1) Marking label information on reels includes (see Fig.8.2.3-1、 Fig.8.2.3-2A/2B):

Fig.8.2.3-2A: Shipping labels

- a). P/O No.
- b). Customer Part No.
- c). Sunlord Part No.
- d). Quantity..
- e). Lot No.
- f). Date code
- g). Inspection stamp
- h). MFG address as 'Made In China'




Fig.8.2.3-



Fig.9.2.3-2B: Production labels

- a). P/O No.
- b). Quantity..
- c). Lot No.
- d). Inspe No
- e). Inspection stamp
- f). MFG address as 'Made In China'.
- g). sequence number




Fig.9.2.3-2A



Fig.9.2.3-2B

2)Marking label information on inner box

- a). Inner box please refers to Fig.8.2.3-3and Table 8.2.3-1
- b). Marking Label on inner box

N/A

3)Marking on outer case (see Fig.8.2.3-5~7 ):

Out case size please refers to Table 8.2.3-2.

- a). Manufacturer: Sunlord ID:  
"Shenzhen Sunlord Electronics Co., Ltd."
- b). Packing label include the following:
  - i) Customer
  - ii) Manufacturer
  - iii) Date code
  - iv) C/No.

Example; "1/10" means that this case is the 1st one Of total 10 cases

- v) P/O No.
- vi) Customer Part No.
- vii) Sunlord Part No.
- viii) Quantity.
- ix) Inspection Stamp.




Fig.8.2.3-3

[Table 8.2.3-1]

Packaging type	A(mm)	B(mm)	C(mm)
Inner box	340	30	340

[Table 8.2.3-2]

Packaging type	L(mm)	W(mm)	H(mm)
TYP1	380	380	250
TYP2	380	380	190




Fig. 8.2.3-5













Fig.8.2.3-6



9 Visual inspection standard of product

File No:		Applied to Wire Wound SMD Power Inductor Series		REV:01
Effective date:				
No.	Defect Item	Graphic	Rejection identification	Acceptance
1	Core defect		The defect length/width ( $l$ or $w$ ) more than $L/6$ or $W/6$ , NG.	AQL=0.65
2	Core crack		Visual cracks, NG.	AQL=0.65
3	Starvation		<ul style="list-style-type: none"> <li>① Resin starved length, <math>l</math>, more than <math>L/2</math>, NG.</li> <li>② IF <math>W &gt; 2\text{mm}</math>, resin starved width, <math>w</math>, more than <math>W/2</math>, NG.</li> <li>③ IF <math>W \leq 2\text{mm}</math>, resin starved width, <math>w</math>, don't control.</li> </ul>	AQL=0.65
4	Excessive glue		The length, width or height of product beyond specified value, NG.	AQL=0.65
5	Cold solder		cold solders $l$ more than 1 mm, NG.	AQL=0.65
6	Solder icicle		<ul style="list-style-type: none"> <li>① The height <math>H</math> of product beyond specified value, NG;</li> <li>② The clearance <math>\Delta f</math> beyond specified value listed in <b>Item 4</b> NG;</li> </ul>	AQL=0.65
7	Electrode uneven		The clearance $\Delta f$ beyond specified value listed in <b>Item 4</b> , NG;	AQL=0.65
8	Marking defect		<ul style="list-style-type: none"> <li>① The content of marking 1) is indistinct, 2) disagrees with current product P/N requirements, NG;</li> <li>② Intersection angle by L1 and L2 more than <math>45^\circ</math>, NG.</li> </ul>	AQL=0.65

**10 Recommended Soldering Technologies**

**10.1 Re-flowing Profile:**

- △ Preheat condition: 150 ~200°C/60~120sec.
  - △ Allowed time above 217°C: 60~90sec.
  - △ Max temp: 260°C
  - △ Max time at max temp: 5sec.
  - Solder paste: Sn/3.0Ag/0.5Cu
  - △ Allowed Reflow time: 2x max
- Please refer to Fig. 10.1-1.




Fig. 10.1-1

[Note: The reflow profile in the above table is only for qualification and is not meant to specify board assembly profiles. Actual board assembly profiles must be based on the customer's specific board design, solder paste and process, and should not exceed the parameters as the Reflow profile shows.]

**10.2 Iron Soldering Profile**

- △ Iron soldering power: Max. 30W
  - △ Pre-heating: 150°C/60sec.
  - △ Soldering Tip temperature: 350°C Max.
  - △ Soldering time: 3sec. Max.
  - △ Solder paste: Sn/3.0Ag/0.5Cu
  - △ Max.1 times for iron soldering
- Please refer to Fig. 10.2-1.




Fig.10.2-1

[Note: Take care not to apply the tip of the soldering iron to the terminal electrodes.]

**11 Precautions**

**11.1 Surface mounting**

- Mounting and soldering condition should be checked beforehand.
- Applicable soldering process to this product is reflow soldering only.
- Recommended conditions for repair by soldering iron:
  - Preheat the circuit board with product to repair at 150°C for about 1 minute.
  - Put soldering iron on the land-pattern.
  - Soldering iron's temperature: 350°C maximum/Duration: 3 seconds maximum/1 time for each terminal.
  - The soldering iron should not directly touch the inductor.
  - Product once removes from the circuit board may not be used again.

**11.2 Handling**

- Keep the products away from all magnets and magnetic objects.
- Be careful not to subject the products to excessive mechanical shocks.
- Please avoid applying impact to the products after mounted on pc board.
- Avoid ultrasonic cleaning.
- It is recommended to use automatic plate division by equipment instead of manual plate splitting to avoid affecting the peeling strength of the electrode.
- Hard tweezers cannot be used to grip the product, it is recommended to use a nozzle pen to prevent damage to the insulation of the product..

**11.3 Storage**

- To maintain the solderability of terminal electrodes and to keep the packing material in good condition, temperature and humidity in the storage area should be controlled.
- Recommended conditions: -10°C~40°C, 70%RH (Max.)
- Even under ideal storage conditions, solderability of products electrodes may decrease as time passes. For this reason, product should be used with one year from the time of delivery.
- In case of storage over 12 months, solderability shall be checked before actual usage.

**11.4 Regarding Regulations**

- Any Class- I or Class-II ozone-depleting substance (ODS) listed in the Clean Air Act in US for regulation is not included in the products or applied to the products at any stage of whose manufacturing processes.
- Certain brominated flame retardants (PBBs, PBDEs) are not used at all.
- The products of this specification are not subject to the Export Trade Control Order in China or the Export Administration Regulations in US.

**11.5 Guarantee**

- The guaranteed operating conditions of the products are in accordance with the conditions specified in this specification.
- Please note that Sunlord takes no responsibility for any failure and/or abnormality which is caused by use under other than the aforesaid operating conditions.

Appendix A: Electrical Characteristics

Customer P/N	Part Number	Inductance	Min. Self-resonant frequency	DC Resistance		Saturation Current		Heat Rating Current		Marking
		100kHz/1V		Max.	Typ.	Max.	Typ.	Max.	Typ.	
	Units	µH	MHZ	Ω	Ω	A	A	A	A	
	Symbol	L	SRF	DCR		Isat		Irms		-
	SWPA5040SR22MT	0.22 ±20%	289	0.008	0.006	18.00	20.00	6.50	7.50	R22
	SWPA5040SR24NT	0.24 ±30%	251	0.008	0.006	15.70	18.00	6.40	7.40	R24
	SWPA5040SR47MT	0.47 ±20%	171	0.009	0.007	10.00	11.50	6.60	7.60	R47
	SWPA5040S1R0NT	1.0 ±30%	117	0.016	0.012	7.35	8.20	4.90	5.10	1R0
	SWPA5040S1R2NT	1.2±30%	110	0.021	0.016	6.50	7.10	4.15	4.30	1R2
	SWPA5040S1R5NT	1.5±30%	86	0.020	0.015	6.30	7.30	4.30	4.80	1R5
	SWPA5040S1R8MT	1.8±20%	55	0.021	0.016	5.50	6.40	4.15	4.30	1R8
	SWPA5040S2R2NT	2.2±30%	50	0.025	0.019	4.90	5.60	3.80	4.30	2R2
	SWPA5040S2R7NT	2.7±30%	37	0.029	0.022	4.30	5.10	3.60	4.10	2R7
	SWPA5040S3R0NT	3±30%	37	0.029	0.022	4.15	4.80	3.60	4.20	3R0
	SWPA5040S3R3NT	3.3 ±30%	32	0.031	0.024	3.95	4.60	3.40	3.90	3R3
	SWPA5040S3R6MT	3.6±20%	30	0.031	0.026	3.80	4.40	3.30	3.70	3R6
	SWPA5040S3R9NT	3.9 ±30%	29	0.035	0.027	3.55	4.20	3.20	3.70	3R9
	SWPA5040S4R7NT	4.7±30%	28	0.039	0.030	3.50	3.90	3.00	3.30	4R7
	SWPA5040S5R6MT	5.6±20%	27	0.046	0.035	3.00	4.10	2.80	3.10	5R6
	SWPA5040S6R8MT	6.8±20%	21	0.056	0.043	2.90	3.50	2.50	2.80	6R8
	SWPA5040S8R2MT	8.2±20%	20	0.062	0.048	2.70	3.00	2.30	2.60	8R2
	SWPA5040S100MT	10±20%	18	0.083	0.064	2.35	2.90	2.10	2.40	100
	SWPA5040S120MT	12±20%	14	0.100	0.077	2.2	2.5	2.0	2.1	120
	SWPA5040S150MT	15±20%	13	0.112	0.086	2.00	2.30	2.00	2.10	150
	SWPA5040S180MT	18±20%	12	0.155	0.119	1.70	2.00	1.45	1.65	180
	SWPA5040S220MT	22±20%	11	0.168	0.129	1.60	1.90	1.50	1.60	220
	SWPA5040S270MT	27±20%	9.8	0.244	0.188	1.52	1.75	1.10	1.25	270
	SWPA5040S330MT	33±20%	9	0.244	0.188	1.30	1.50	1.20	1.40	330
	SWPA5040S470MT	47±20%	7	0.354	0.272	1.10	1.30	1.00	1.10	470
	SWPA5040S510MT	51±20%	6	0.494	0.380	1.00	1.20	1.00	1.10	510
	SWPA5040S560MT	56±20%	6	0.494	0.380	1.05	1.20	0.80	0.90	560
	SWPA5040S680MT	68±20%	6	0.520	0.400	0.90	1.10	0.80	0.90	680
	SWPA5040S750MT	75±20%	6	0.585	0.450	0.85	0.95	0.72	0.80	750
	SWPA5040S101MT	100±20%	5	0.728	0.560	0.75	0.90	0.70	0.80	101
	SWPA5040S151MT	150±20%	3.7	0.975	0.750	0.65	0.67	0.60	0.70	151
	SWPA5040S221MT	220±20%	3.0	1.82	1.40	0.48	0.55	0.40	0.50	221
	SWPA5040S301MT	300±20%	2.7	2.60	2.00	0.50	0.58	0.35	0.40	301
	SWPA5040S331MT	330±20%	2.7	2.73	2.10	0.42	0.47	0.40	0.50	331
	SWPA5040S471MT	470±20%	2.7	3.90	3.00	0.37	0.43	0.35	0.40	471
	SWPA5040S561MT	560±20%	1.5	4.92	3.78	0.31	0.36	0.31	0.35	561
	SWPA5040S681MT	680±20%	1.6	5.07	3.90	0.30	0.35	0.25	0.30	681

Note:※1 : Rated current:  $I_{sat}$  (max.) or  $I_{rms}$  (max.), whichever is smaller;

※2 : Saturation Current: Max.Value, DC current at which the inductance drops less than 30% from its value without current;

Typ. Value, DC current at which the inductance drops 30% from its value without current;

※3 :  $I_{rms}$ : DC current that causes the temperature rise ( $\Delta T$ ) from 20°C ambient.

For Max. Value,  $\Delta T < 40^\circ C$ ; for Typ. Value,  $\Delta T$  is approximate 40°C.

The part temperature (ambient + temp. rise) should not exceed 125 °C under worst case operating conditions. Circuit design, component placement, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.

Typical Electrical Characteristics:

